

SP2200 TICKET PRINTER

Now
Mettler-Toledo
Indicator
Compatible

- Double-strike high speed, 180 character per second (cps)
- Up to five-part multicopy forms
- Functions in slave capacity, printing information sent via RS-232 or weight extraction mode, processing information before printing
- Cash drawer kick-out function
- Inexpensive ink cartridge for no-mess ribbon changes
- Battery backup: optional time/date and consecutive number (or ID) are retained for a year or more in the event of a power failure



PART #	DESCRIPTION	EST. SHIP WEIGHT
34229	SP2200 Ticket Printer with RS-232 (black & light gray)	12 lb
34178	SP2200 Ticket Printer with RS-232 (light gray)	12 lb
40867	SP2200 Ticket Printer with RS-232 (blue & gray)	12 lb
35855	SP2200 Ticket Printer 230 VAC with RS-232 (black & light gray)	12 lb
35853	SP2200 Ticket Printer 230 VAC with RS-232 (light gray)	12 lb
40894	SP2200 Ticket Printer 230 VAC with RS-232 (blue & gray)	12 lb

OPTIONS/ACCESSORIES

34228	SP2200 Ticket Printer with RS-232, time, date and switch module (black & light gray)
34227	SP2200 Ticket Printer with RS-232, time, date and switch module (light gray)
40868	SP2200 Ticket Printer with RS-232, time, date and switch module (blue & gray)
35856	SP2200 Ticket Printer 230 VAC with RS-232, time, date and switch module (black & light gray)
35854	SP2200 Ticket Printer 230 VAC with RS-232, time, date and switch module (light gray)
40895	SP2200 Ticket Printer 230 VAC with RS-232, time, date and switch module (blue & gray)
23170	Centronics® parallel interface adapter
20302	20 mA current loop
23169	RS-422
20308	Ink cartridge, black
22597	Ink cartridge, red (minimum order 12)
22596	Ink cartridge, blue (minimum order 12)
21210	Scale veil (protective dust cover)
34282	Maintenance and service manual
34171	Additional operating manual

CABLES

15548	25-pin 20 mA serial interface cable
15568	25-pin RS-232 serial interface cable <i>Interfaces to: IQ5000 and UMC2000 with simplex RS-232 or 6-pack multiple serial expansion board</i>
15547	Blunt End, 20 mA/RS-232 serial interface cable <i>Interfaces to: UMC444, UMC555, IQ600HB, IQ700HB, IQ plus 800/810, IQ plus 310A, IQ plus 355, 390-DC, 590-DC, IQ plus 510, and IQ plus 710</i>
15565	Custom 20 mA/RS-232 serial interface cable <i>Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type. Standard cable length is 5 feet. \$2.00 charge for each additional foot.</i>