


## 320IS Plus Intrinsically-Safe Digital Weight Indicator



FM Entity Approved for use in hazardous locations per Rice Lake Weighing Systems control drawing file number 72717.

**\*Exclusions:** The following load cells cannot be used with the 320IS: RL71000HE, RL8000HE, RL8000KM, RLBEAM, and RL32155.

**CAUTION!** The equipment contained within this Explosive Environment section requires greater attention to specification and installation guidelines. Improper specification, installation, or service of these products can result in loss of equipment or serious injury.



### Standard Features

- Bright Light Emitting Diode (LED)
- Stainless steel NEMA 4X/IP66 enclosure
- T4 temperature rating
- Front-panel digital calibration
- Automatic zero and span temperature compensation
- Excitation for four 350Ω or eight 700Ω load cells
- Gross/Tare/Net computation
- Tilt stand
- Factory Mutual (FM) Entity approved
- Duplex fiber optic interface
- Power ON/OFF; battery save mode
- I/O Module Option: 2 serial ports, 2 analog outputs, 4 digital inputs, 4 relay contact outputs.
- 8 setpoint (requires I/O module)
- Factory Mutual (FM) entity approved for classes I, II, and III; Divisions 1 and 2; Groups A, B, C, D, E, F, and G
- Time & Date (requires I/O module)

Intrinsically Safe

### Specifications

#### LOAD CELL EXCITATION:

3.0 VDC @ 87.5Ω  
4.6 VDC @ 700Ω

#### LOAD CELL CURRENT:

34 mA (4 x 350Ω load cells) or  
(8 x 700Ω load cells)

#### LOAD CELL CABLING:

4 and 6-wire with remote sensing  
(recommended)

#### ANALOG SIGNAL INPUT RANGE:

0.6 mV/V - 4.0 mV/V

#### ANALOG SIGNAL SENSITIVITY:

0.2 μV/graduation minimum  
1.5 μV/graduation recommended

#### CONVERSION RATE:

60 updates/second

#### INTEGRATION TIME:

20 mSec typical

#### RESOLUTION:

10,000 displayed graduations  
(NTEP), 100,000 expanded  
The maximum number of allowed  
graduations will vary by application

#### DISPLAY INCREMENTS:

1, 2, 5

#### DISPLAY:

Six digits, Light Emitting Diode (LED);  
16-segment, 0.8 in (20mm) digits

#### DECIMAL POINT:

Configurable with dead zeros

#### UNIT SWITCHING:

Configurable for two units of  
measurement with front panel  
operation with conversion for tare  
and setpoint values

#### FRONT-PANEL CONTROL SWITCHES:

Zero, Gross/Net, Tare, Print, Units  
Conv, Start, Stop, Accum, Tare  
Display

#### FRONT PANEL:

24-button flat membrane panel

#### FRONT-PANEL LED ANNUNCIATORS:

Center Zero, Gross, Net, Motion, lb,  
kg, oz, g

#### MOTION BAND:

Configurable to ±1 or ±3  
graduations, 1 second delay (or Off)

#### POWER INPUT:

5.8 - 7.9 VDC, 100 - 175mA  
Maximum power consumption 0.25  
watts

#### OPERATING TEMPERATURE:

14°F to 104°F (-10°C to 40°C) legal

#### RATING/MATERIAL:

Stainless steel NEMA 4X/IP66  
enclosure

#### OPTIONAL BATTERY:

Operating Times: 4 x 350Ω =  
35-40 hrs. 1 x 350Ω = 40-50 hrs.  
Charging Times: 10 hours for dead  
battery, 14 hours for initial charge

#### WEIGHT:


6.1 lb (2.8 kg)

#### APPROVALS:

NTEP pending (TUV, C (UL),  
FM Entity)  
Measurement Canada Approved:  
AM-5560

#### WARRANTY:

One-year limited warranty



### DIMENSIONS

#### Without battery

A = 8.56" (217.4 mm)    B = 6.00" (152.4 mm)  
C = 9.50" (241.3 mm)    D = 2.64" (67.1 mm)  
E = 3.75" (95.2 mm)

#### With optional battery and tilt stand

F = 11.56" (293.6 mm)    G = 4.75" (120.7 mm)

#### Optional I/O Module


12.90" x 11.63" x 6.25"  
(327.7mm x 295.4mm x 158.8mm)

#### Optional Power Supply

7.00" x 5.13" x 3.125"  
(177.8mm x 130.0mm x 79.375mm)

# 320IS Plus

## Specifications (continued)



\*I/O module required for anything besides basic weighing

Intrinsically Safe

PART #	DESCRIPTION	PRICE
91235	320IS Plus Intrinsically-Safe Digital Weight Indicator full keypad with battery pack and charger & tilt stand.....	\$1,927.00
91236	320IS Plus Intrinsically-Safe Digital Weight Indicator full keypad with A/C power supply .....	1,940.00
86240	320IS Plus indicator only.....	1,195.00
<b>Hazardous Environment Cable and Fiber Optic Cable</b>		
32817	EL147IS hazardous environment cable .....	2.65/ft
72241	Hazardous environment 3 conductor .....	3.75/ft
78026	Fiber optic, duplex cable 100 ft.....	130.00
78027	Fiber optic, duplex cable 200 ft.....	258.00
<b>Options/Accessories</b>		
72713	Power supply, IS-EPS-100-240VAC.....	745.00
72725	IS-6V battery option with cable adapter .....	535.00
74001	Battery charger, 115VAC.....	145.00
74002	Battery charger, 115/230VAC .....	535.00
80662	Fuse, fast acting 200mA 250V, 5x20mm, Littelfuse (replacement part for the IS-EPS-100-240VAC power supply).....	2.50
80869	Fuse, 1.25A, 250V TR5 time-lag (replacement part for the I/O Module).....	2.50
72726	Tilt stand (required for battery model).....	57.00
89239	I/O Module, stainless steel NEMA 4 enclosure, safe area option (requires fiber optic cable, AC power required).....	995.00
83388	Timer relay kit includes din rail, timer relay for latching and mount.....	370.00
85353	Installation manual .....	35.00
78076	I/O Module manual .....	30.00

Rice Lake Weighing Systems™ warrants that all Rice Lake Weighing Systems Intrinsically Safe (IS) equipment and systems installed by a distributor or Original Equipment Manufacturer (OEM) will operate per written specifications as confirmed by the Distributor/OEM and accepted by Rice Lake Weighing Systems. All systems and components are warranted against defects in materials and workmanship for one year.

All Rice Lake Weighing Systems Intrinsically Safe equipment carries a Factory Mutual approval and is documented on various control drawings. Each device is manufactured Rice Lake Weighing Systems factory. To preserve the warranty and Factory Mutual approval, all repairs or replacement of circuit boards or components housed within the enclosures must be performed by Rice Lake Weighing Systems factory authorized personnel.

**CAUTION!** The equipment contained within this Explosive Environment section requires explicit attention to specification and installation guidelines. Improper specification, installation or service of these products can result in loss of equipment and/or serious injury.