

EPSON TM-U295 Ticket Printer



Standard Features

- High-speed 1.9 to 2.3 lines per second printing
- Single copy or up to four-part multicopy ticket printing
- Functions in slave capacity, printing information sent via RS-232

Approvals



Specifications

PRINT SPEED:

1.9 to 2.3 lines per second (5 x 7 character, 3 dot line spacing)

COLUMN CAPACITY:

35/42 columns

CHARACTERS PER LINE:

35 standard font

PRINT AREA:

2.59" W (65.8 mm W)

CHARACTER FORMATION:

5 x 7 and 7 x 7 dot matrix

CHARACTER HEIGHT:

0.11 standard font

CHARACTER SET:

Full 96-character ASCII; with software control, 32 international characters, 128 x 2 graphic characters

LINE SPACING:

0.16" (4.06 mm) software programmable in 1/60" units

PRINthead LIFE:

Approximately 100 million strokes/pin

FORM THICKNESS:

Single-ply - 0.003" to 0.009"
(0.08 to 0.23 mm)
Copy paper - 0.003" to 0.014"
(0.08 to 0.36 mm)

RIBBON:

Cassette-type purple ribbon. Ribbon life is approximately 1.5 million characters (continuous prints). Black ink also available.

SERIAL INTERFACES:

RS-232 compatible (25-pin D-sub)

BAUD RATES:

1200, 2400, 4800, 9600, selectable

PARITY:

7 or 8 bits, none, even or odd

STOP BITS:

1 or more

HANDSHAKING:

DTR/DSR or XON/XOFF control selectable

OVERALL DIMENSIONS:

7.08" W x 7.49" D x 3.99" H
(180 mm W x 190.5 mm D x 101.5 mm H)

APPROVALS:

UL listed, CSA certified, CE marked

WARRANTY:

One-year limited warranty (includes printhead)

EPSON TM-U295

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
23113	TM-U295 Ticket Printer, RS-232, 115/230 VAC w/power supply	9 lb	\$614.00
35891	TM-U295 Ticket Printer, 115/230 VAC w/RS-232 and power supply, 25 DB to blunt end cable	9 lb	660.00
33816	TM-U295 Ticket Printer, RS-232, 24 VDC	9 lb	583.00
Options/Accessories			
29582	Scale veil (protective dust cover)		54.00
29584	Ink cartridge (purple)		12.00
29583	Ink cartridge (black)		12.00
23112	Power supply		104.00
34344	Additional operating manual		16.00
72309	Power supply, 12 VDC cigarette plug		181.00
Cables			
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable		52.00
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable		52.00
41279	25-pin D-sub male to 9-pin D-sub male, RS-232 with handshaking <i>Interfaces with DC-190, DC-100, DC-200, DC-300</i>		52.00
32810	25-pin D-sub male to 8-pin D-sub male, RS-232 with handshaking <i>Interfaces with DC-190, DC-100, DC-200, DC-300</i>		52.00
Consult*	Custom 20 mA/RS-232 serial interface cable		98.00

**Custom cables are designed to interface with your specific equipment.
Please specify equipment model number and connector type.
Standard cable length is 5 feet. \$2.00 charge for each additional foot.*