

EPSON TM-U220 Tape Printer



Approvals



Standard Features

- 9-Pin Dot Matrix print head
- High-speed 4.7 to 6.0 lines per second printing
- Drop-in paper set and auto paper loading
- Automatically transmits changes in printer status
- RS-232
- Optional connect-it cartridges for parallel, USB, 10 Base-T

Specifications

PRINT SPEED:

Approximately 4.7 lines per second

COLUMN CAPACITY:

40/42 or 33/35 columns

CHARACTERS PER LINE:

40 characters

PRINT AREA:

3" (76.2 mm) wide

CHARACTER FORMATION:

7 x 9 & 9 x 9 dot matrix

CHARACTER HEIGHT:

0.12 standard font

CHARACTER SET:

95 alphanumeric characters,
37 international characters,
128 x 12 graphic characters

LINE SPACING:

0.17" (4.32 mm)

PRINTHEAD LIFE:

Approximately 100 million strokes/pin

FORM THICKNESS:

0.002" to 0.003" (0.06 to 0.085 mm)

RIBBON:

Cassette-type purple ribbon. Ribbon life is approximately 1.5 million characters (continuous prints). Black ink also available.

SERIAL INTERFACES:

RS-232 compatible (25-pin D-sub)

BAUD RATES:

4800, 9600

PARITY:

7 or 8 bits, none, even or odd

STOP BITS:

1 or more

HANDSHAKING:

DTR/DSR or XON/XOFF control
selectable

OVERALL DIMENSIONS:

Type A: 6.3" W x 11.3" D x 6.2" H
(160 mm W x 286 mm D x 157.5 mm H)

Type D: 6.3" W x 9.7" D x 5.4" H
(160 mm W x 248 mm D x 138.5 mm H)

APPROVALS:

UL listed, CSA-certified, CE marked

WARRANTY:

Two-year limited warranty (includes
printhead)

EPSON TM-U220

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
81076	TM-U220D, RS-232, 115/230 VAC	10 lb	\$408.00
81077	TM-U220A, internal rewind and cutter, RS-232, 115/230 VAC	10 lb	614.00
Options/Accessories			
83007	Parallel option connect-it cartridge		62.00
35666	Protective dust cover		57.00
31296	Ink cartridge (purple)		12.00
*66499	Ink cartridge (black and red)		12.00
69916	One-ply paper roll, 3" W x 150' L (76.2 mm W x 45.7 m L)		5.00
69915	Two-ply paper roll, 3" W x 90' L (76.2 mm W x 27.4 m L)		7.00
35667	Additional operating manual		16.00
72309	Power supply, 12 VDC cigarette plug		181.00
23112	115 VAC power supply (included with printer)		104.00
Cables			
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable		52.00
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable		52.00
Consult	Custom 20 mA/RS-232 serial interface cable		98.00

*Custom cables are designed to interface with your specific equipment.
Please specify equipment model number and connector type.
Standard cable length is 5 feet. \$2.00 charge for each additional foot.
*Red/Black ribbon to turn on ASCII code-27,1,14,48 ON
27,1,14,49 OFF*