

## SP2200 Ticket Printer



### Standard Features

- Double-strike high speed, 180 characters per second (cps)
- Single copy or up to five-part multicopy forms
- Functions in slave capacity, printing information sent via RS-232 or weight extraction smart mode, processing information before printing
- Cash drawer kick-out function
- Inexpensive ink cartridge for no-mess ribbon changes
- Battery backup; optional time/date and consecutive number (or ID) are retained for a year or more in the event of a power failure
- Compatible with most Mettler-Toledo indicators

### Approvals



## Specifications

### PRINT SPEED:

3.5 lines per second, 180 characters per second

### CHARACTERS PER LINE:

40 characters at 12 cpi  
Print Area: 3.33" (84.6 mm) wide

### CHARACTER FORMATION:

5 x 9 dot matrix

### CHARACTER HEIGHT:

0.1" (2.5 mm) enhanced double-wide or 0.45" (11.4 mm) on 4X. Can be inverted for left side of tickets

### CHARACTER SET:

Full 96-character ASCII (upper and lower case set)

### DIMENSIONS:

7" H x 8" W x 11" L

### LINE SPACING:

Six lines per inch (25.4 mm)

### COPY CAPABILITIES:

Single copy or up to five-part multicopy forms

### PRINT MEDIA:

Form thickness adjustable from 0.004" to 0.026" (0.1 to 0.7 mm) by 0.004" step increments

### RIBBON:

Cartridge-type black or blue ink ribbon. Ribbon life is approximately 1 million standard characters

### SERIAL INTERFACES:

RS-232 standard, 20 mA current loop (passive only) or Centronics® Parallel

### WEIGHT:

12 lbs

### BAUD RATES:

300, 600, 1200, 2400, 4800, 9600 or 19,200 selectable

### PARITY:

1 parity bit (even ignored by printer)

### APPROVALS:

UL & C-UL listed, CE marked

### WARRANTY:

One-year limited warranty (includes printhead)

# SP2200

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
34229	SP2200 Ticket Printer, 115 VAC w/RS-232 (black/light gray)	12 lb	\$1,295.00
35855	SP2200 Ticket Printer, 230 VAC w/RS-232 (black/light gray)	12 lb	1,295.00
<b>SP2200 with time/date and switch module</b>			
34228	SP2200 Ticket Printer, 115 VAC w/RS-232 (black/light gray)	12 lb	1,395.00
35856	SP2200 Ticket Printer, 230 VAC w/RS-232 (black/light gray)	12 lb	1,395.00
<b>Options/Accessories</b>			
35231	Switch module		85.00
20232	Time/date clock chip		85.00
23170	Centronics® parallel interface adapter		90.00
20302	20 mA current loop		72.00
20308	Ink cartridge (black)		24.00
21210	Protective dust cover		55.00
34282	Maintenance and service manual		27.00
34171	Additional operating manual		27.00
<b>Cables</b>			
15548	25-pin D-sub male to 25-pin D-sub male 20 mA serial interface cable		52.00
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable		52.00
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable		52.00
	<i>Interfaces to: UMC555, UMC600, IQ700, IQ plus 355, IQ plus 390-DC, IQ plus 510, IQ plus 590-DC, IQ plus 710, 520 and 920i</i>		
Consult	Custom 20 mA/RS-232 serial interface cable		98.00
	<i>Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type. Standard cable length is 5 feet. \$2.00 charge for each additional foot.</i>		